



### BRSW221

- Direct radiating subwoofer with high performance.
- Includes a two 21" ceramic low weight loudspeakers of high magnetic strength and big thermal dissipation.
- This cabinet permits low frequency range sat a high SPL level, the bass reflex system works from 22 Hz.

This subwoofer is designed to play with high energy low frequencies, unlike high performance subwoofers this cabinet has an extended range of the whole frequency band typical of a subwoofer, from 25 Hz to 150 Hz is linear, distinguishing for example all the bassist's notes for example. The performance of this gabinete is ideal for big concerts. This cabinet is made of birch Wissa-Plywood, Speakon NL4 connectors are used for power amplifier conections . The paint finish is high resintance polyurea.

#### TECHNICAL DATA

#### BRSW 221

Trasducers

2 X 21"

Coverage

-

Nominal impedance

4 Ohms.

Power AES

2800 W

Maximun Peak SPL

143 dB SPL

Frecuency Range

22 Hz to 150 Hz

Sensibility (1 W@ 1m)

1 w @ 1 m: 105 dB

Weigth

118 Kg.

Enclosure Geometry

Rectangular

Angle adjustment

-

Dimensions (WxHxD)

1239 x 654 x 863 mm.

Enclosure Material

Birch Plywood 21 mm.

Riggings

-

Finish

Polyurea

Colour

Black

Connection

2 x Speakon NL4

