



SPECIFICATIONS

- Conventional compact size cabinet.
- Includes one 10" transducer and one 1" compression driver mounted on a rotary constant directivity horn.

The ARQ speaker series have been designed for use in discrete PA systems as well as for fixed installation. The high frequency horns are rotatable which enables to install them in horizontal and/or vertical position. The ARQ series have a curved design made in Birch wood, it is also ideal for installations where a good quality sound and elegant design is required. A high quality two-way passive crossover is included into each cabinet. This cabinet is made of birch Wissa-Plywood. Speakon NL4 connectors are used for power amplifier connections. The paint finish is high resistance polyurea.

TECHNICAL DATA	ARQ10
Transducers	1 X 10" - 1 X 1"
Coverage	90° x 40° Rotating
Nominal impedance	LF 8Ω - HF 8Ω
Power AES	300W
Maximun Peak SPL	120 dB SPL
Frecuency Range	50 Hz to 18 kHz
Sensibility(1 W@ 1m)	1 w@ 1 m: 97 dB
Weigth	16 Kg
Enclosure Geometry	Elliptical Trapezoidal
Angle adjustment	-
Dimensions(WxHxD)	300 x 530 x 345 mm
Enclosure Material	Birch Plywood 15 mm
Rigging	M8
Finish	Polyurea
Colour	Black
Connections	2 x Speakon NL4

