

# ARQ12

ARQ SERIES



## SPECIFICATIONS

- Conventional compact size cabinet.
- Includes an 12" transducer and a 1" compression driver mounted on a rotary constant directivity horn.

*The ARQ speaker series have been designed for use in discrete PA systems as well as for fixed installation. The high frequency horns are rotatable which enables to install them in horizontal and/or vertical position.*

*The ARQ series have a curved design made in Birch wood, it is also ideal for installations where a good quality sound and elegant design is required. A high quality two-way passive crossover is included into each cabinet.*

*This cabinet is made of birch Wissa-Plywood. Speakon NL4 connectors are used for power amplifier connections.*

*The paint finish is high resistance polyurea.*

TECHNICAL DATA	ARQ12
Transducers	1 X 12" / 1 X 1"
Coverage	90° x 40° Rotating
Nominal impedance	LF 8 HF 8
Power AES	500W
Maximum Peak SPL	126 dB SPL
Frequency Range	45 Hz to 18 kHz
Sensitivity (1 W @ 1 m)	1 w @ 1 m: 98 dB
Weight	26 Kg.
Enclosure Geometry	-
Angle adjustment	Elliptical Trapezoidal
Dimensions (W x H x D)	350 x 590 x 365 mm.
Enclosure Material	Birch Plywood 15 mm.
Rigging	M8
Finish	Polyurea
Colour	Black
Connections	2 x Speakon NL4

