

ARQ 15

ARQ SERIES



SPECIFICATIONS

- Conventional compact size cabinet.
- Includes one 15" transducer and one 1" compression driver mounted on a rotary constant directivity horn.

The ARQ speaker series have been designed for use in discrete PA systems as well as for fixed installation. The high frequency horns are rotatable which enables to install them in horizontal and/or vertical position. The ARQ series have a curved design made in birch wood, ideal for installations where a good quality sound and elegant design are required. A high quality two-way passive crossover is included into each cabinet. This cabinet is made of birch Wissa-Plywood. Speakon NL4 connectors are used for power amplifier connections. The paint finish is made of high resistance polyurea.

TECHNICAL DATA	ARQ15
Transducers	1X 15" / 1X 1"
Coverage	90° x 40° Rotating
Nominal impedance	LF 8Ω - HF 8Ω
Power AES	600W
Maximun Peak SPL	127 dB SPL
Frecuency Range	40 Hz to 18 kHz
Sensibility(1W@ 1m)	1w @ 1m: 98 dB
Weigth	30 Kg
Enclosure Geometry	Elliptical Trapezoidal
Angle adjustment	-
Dimensions(WxHxD)	415 x 648 x 401 mm
Enclosure Material	Birch
Rigging	Plywood 18 mm
Finish	M8Polyurea
Colour	Black
Connections	2 x Speakon NL2 neutrik

