



## SPECIFICATIONS

- Gabinete convencional de tamaño compacto.
- Incluye un transductor de 15" y un motor de compresión de 1" montado en una bocina rotativa de directividad constante.

*The ARQ speaker series have been designed for use in discrete PA systems as well as for fixed installation. The high frequency horns are rotatable which enables to install them in horizontal and/or vertical position.*

*The ARQ series have a curved design made in Birch wood, it is also ideal for installations where a good quality sound and elegant design is required. A high quality two-way passive crossover is included into each cabinet.*

*This cabinet is made of birch Wissa-Plywood. Speakon NL4 connectors are used for power amplifier conexions.*

*The paint finish is high resintance polyurea.*

TECHNICAL DATA	ARQ15
Transducers	1X 15" / 1X 1"
Coverage	90° x 40° Rotating
Nominal impedance	LF 8Ω – HF 8Ω
Power AES	600W
Maximun Peak SPL	127 dB SPL
Frecuency Range	40 Hz to 18 kHz
Sensibility(1 W@ 1m)	1w @ 1m: 98 dB
Weigth	30 Kg
Enclosure Geometry	Elliptical Trapezoidal
Angle adjustment	-
Dimensions(WxHxD)	415 x 648 x 401 mm
Enclosure Material	Birch
Rigging	Plywood 18 mm
Finish	M8Polyurea
Colour	Black
Connections	2 x Speakon NL2 neutrik

