



## SPECIFICATIONS

- Conventional compact size cabinet.
- Includes an 8" transducer and a 1" compression driver mounted on a rotary constant directivity horn.

The ARQ speaker series have been designed for use in discrete PA systems as well as for fixed installation. The high frequency horns are rotatable which enables to install them in horizontal and/or vertical position.

The ARQ series have a curved design made in Birch wood, it is also ideal for installations where a good quality sound and elegant design is required. A high quality two-way passive crossover is included into each cabinet.

This cabinet is made of birch Wissa-Plywood. Speakon NL4 connectors are used for power amplifier connections.

The paint finish is high resistance polyurea.

TECHNICAL DATA	ARQ8
Transducers	1 X 8" / 1 X 1"
Coverage	80 X 60°
Nominal impedance	LF 8 HF 8
Power AES	250W
Maximun Peak SPL	119dB SPL
Frecuency Range	65 Hz to 18 kHz
Sensibility(1 W@ 1m)	1 w@ 1 m: 96 dB
Weigth	11 Kg.
Enclosure Geometry	Elliptical Trapezoidal
Angle adjustment	-
Dimensions(WxHxD)	242 x 410 x 284 mm.
Enclosure Material	Birch Plywood 12 mm.
Rigging	M8
Finish	Polyurea
Colour	Black
Connections	2 x Speakon NL4

