

F 208



NEW PRODUCT

SPECIFICATIONS

- Two-way frontfill system.
- Includes two 8" neodymium speakers with high magnetic capacity and sensitivity.
- 1.4" neodymium compression driver coupled to a W&dB waveguide
- This unit is made of Baltic birch and the metal parts are made of galvanized steel.
- The dispersion pattern is 120°x 7°.
- Offered in self-powered or passive version.

This model has been designed as a frontfill system to cover shadow areas on large stages where a high level of SPL and sound quality is required.

This equipment works as a "Full range" system, incorporating a two-channel amplifier of 1500 W each, with programmable DSP.

This model incorporates new high-power transducers that are equivalent to larger components, its performance exceeds most equivalent systems.

TECHNICAL DATA	F 208
Speakers	2 x 8" - 1 x 1,4"
Dispersion	120° x 7°
Rated impedance	4 Ω Low
AES power.	1000 W. Low/ 80 W. High
Max SPL (Peak)	137 dB
Frequency Response	50 / 20 kHz
Sensitivity (1W at 1m)	102 dB
Weight	18 kg
Geometry	Trapezoidal .
Adjustment angle	From 0 to 7 degrees
Dimensions (LxWxD)	681 x 257 x 380 mm.
Type of material	Wissa Plywood Birch
Flying support	Aluminum and steel.
Finish	Polyurethane
Color	Ral letter
Connections	2 x Speakon
Power module	Optional

